

**Vaunix Technology Corporation**  
**Lab Brick® Family of RF Switches**

**Ethernet Based API User**  
**Manual**



**NOTICE**

Vaunix has prepared this manual for use by Vaunix Company personnel and customers as a guide for the customized programming of Lab Brick products. The drawings, specifications, and information contained herein are the property of Vaunix Technology Corporation, and any unauthorized use or disclosure of these drawings, specifications, and information is prohibited; they shall not be reproduced, copied, or used in whole or in part as the basis for manufacture or sale of the equipment or software programs without the prior written consent of Vaunix Technology Corporation.

# Table of Contents

<b>1.0</b>	<b>OVERVIEW .....</b>	<b>4</b>
<b>2.0</b>	<b>USING THE SDK.....</b>	<b>5</b>
<b>3.0</b>	<b>PROGRAMMING .....</b>	<b>6</b>
<b>3.1</b>	<b>Overall Strategy and API architecture .....</b>	<b>6</b>
<b>3.2</b>	<b>Status Codes .....</b>	<b>7</b>
<b>3.3</b>	<b>Functions – Selecting the Device .....</b>	<b>7</b>
<b>3.4</b>	<b>Functions – Setting parameters on the RF Switch .....</b>	<b>9</b>
<b>3.5</b>	<b>Functions – Reading parameters from the RF Switch .....</b>	<b>10</b>
<b>4.0</b>	<b>PROGRAMMING SUPPORT .....</b>	<b>12</b>

## 1.0 OVERVIEW

The LabBrick RF Switch Win32 SDK supports developers who want to control LabBrick RF Switch from Windows programs, or who want to control the RF Switch from LabVIEW<sub>1</sub> or other National Instruments programming environments. The SDK includes a dll which provides a Win32 API to find, initialize, and control the RF Switch, along with header files and an example Win32 C program which demonstrates the use of the API.

## 2.0 USING THE SDK

The SDK consists of a dll, named VNX\_Eth\_Lsw64.dll, along with this documentation, a C style header file, a library file for linking to the dll, and a VC 6 example program. Unzip the SDK into a convenient place on your hard disk, and then copy the dll and library file into the directory of the executable program you are creating. Add the header file (lswdrv.h) to your project and include it with the other header files in your program. Make sure that the linker directives include the path of the library file.

## 3.0 PROGRAMMING

### 3.1 Overall Strategy and API Architecture

The API provides functions for identifying how many and what type of LabBrick RF Switch are connected to the system, initializing RF Switch so that you can send them commands and read their state, functions to control the operation of the RF Switch, and finally a function to close the software connection to the RF Switch when you no longer need to communicate with it.

The API can be operated in a test mode, where the functions will simulate normal operation but will not actually communicate with the hardware devices. This feature is provided as a convenience to software developers who may not have a LabBrick RF Switch with them, but still want to be able to work on an applications program that uses the LabBrick. Of course it is important to make sure that the API is in its normal mode in order to access the actual hardware!

Be sure to call `fnLSW_SetTestMode(FALSE)`, unless of course you want the API to operate in its test mode.

### 3.2 Status Codes

All of the set functions return a status code indicating whether an error occurred. The values of the status error are defined in the `LSWdrv.h` header file.

### 3.3 Functions – Selecting the Device

VNX\_LSW\_API void `fnLSW_SetTestMode`(bool testmode)

Set testmode to FALSE for normal operation. If testmode is TRUE the dll does not communicate with the actual hardware, but simulates the basic operation of the dll functions. It does not simulate the operation of attenuation ramps generated by the actual hardware, but it does simulate the behavior of the functions used to set the parameters for the ramps.

VNX\_LSW\_API void `fnLSW_Init`(void)

This function will be used to initialize LSW device data structures.

VNX\_ATTEN\_LSWSTATUS `fnLSW_InitDevice`(char\* deviceip)

This function is used to open the device interface socket connection over ethernet to the RF Switch and initialize the dll's copy of the device's settings. If the fnLSW\_InitDevice function succeeds, then you can use the various fnLSW\_Get\* functions to read the RF Switch's settings. This function will fail, and return an error status if the RF Switch has already been opened by another program.

VNX\_LSW\_API LSWSTATUS fnLSW\_CloseDevice(char\* deviceip)

This function closes the device socket interface to the RF Switch. It should be called when your program is done using the RF Switch.

VNX\_LSW\_API LSWSTATUS fnLSW\_CheckDeviceReady(char\* deviceip)

This function will be used to check whether device is ready to get/set the parameters of the LSW RF Switch device.

### **3.4 Functions – Setting parameters on the RF Switch**

VNX\_LSW\_API LSWSTATUS fnLSW\_SetSwitchRFoutput(char\* deviceip, int swindex, LSW\_SWPORT\_T swport)

This function is used to set RF switch output port selection based on the input RF switch index.

VNX\_LSW\_API LSWSTATUS fnLDA\_SaveSettings(char\* deviceip)

The LabBrick RF switch can save their settings, and then resume operating with the saved settings when they are powered up. Set the desired parameters, then use this function to save the settings.

### **3.5 Functions – Reading parameters from the RF Switch**

All Get function calls takes two arguments one pointer pointing to the device ip string and other is the response data pointer.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetModelName(char\* deviceip, char \*respdata)

This function is used to get the model name of the RF Switch.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetSerialNumber(char\* deviceip, int\* respdata)

This function is used to get the serial number of the RF Switch.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetSoftwareVersion(char\* deviceip, char\* respdata)

This function is used to read the software version of the device.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetIPMode(char\* deviceip, int\* respdata)

This function is used to read the IP mode configuration of the device. Response data "0" represents the "Static" mode, "1" represents the "DHCP" mode.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetIPAddress(char\* deviceip, char\* respdata)

This function is used to read the IP address of the device.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetNetmask(char\* deviceip, char\* respdata)

This function is used to read the netmask of the device.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetGateway (char\* deviceip, char\* respdata)

This function is used to read the gateway address of the device.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetMaxSwitchDevices(char\* deviceip, int\* respdata)

This function is used to read the max RF switches device.

VNX\_LSW\_API LSWSTATUS fnLSW\_GetSwitchRFoutput(char\* deviceip, int swindex, int\* respdata)

This function is used to read the RF switch output device port status based on the input RF switch index.

## **4.0 PROGRAMMING SUPPORT**

Lab Brick programming support is available from Vaunix Technology Corporation. Please contact our technical support group by email - [LabBrickSupport@Vaunix.com](mailto:LabBrickSupport@Vaunix.com).

Vaunix Technology also offers custom programming solutions. Send us your requirements to receive a fixed rate project quotation.

Thank you for using our Lab Brick products.